

FUTURE OF ELECTRIC PROPULSION

May 20, 2019

John Brophy and Dan Goebel

Jet Propulsion Laboratory

California Institute of Technology



Outline

- Introduction
- Past
- Present
- Future



Introduction

- Why electric propulsion?
- How
- Things to be mindful of when designing an electric propulsion system




Why Electric Propulsion?

$$\frac{m_f}{m_i} = e^{-\frac{v_{s/c}}{v_{ex}}}$$

The faster you want to go, the higher your exhaust velocity must be








Decouple the Propellant from the Energy to Accelerate It

Chemical propulsion systems:

- Carry the energy for propulsion with the propellant
- Power is determined by the propellant mass flow rate
- Performance is limited by the energy density of the propellants

Electric propulsion systems:


- Decouple the energy for propulsion from the propellants – allows more energy to be added to each kg of propellant
- Power is generated on-board by a separate power system
- Performance is limited by the power generated by the power system





Types of Electric Thrusters

➤ Electrothermal → resistively heat the propellant and expand the hot gas through a nozzle



➤ Electrostatic → ionize the propellant and accelerate the ions through an electric field



Electromagnetic → ionize the propellant and accelerate the ions using crossed electric and magnetic fields



Hall Thrusters




Types of Power Sources


Solar Arrays



Radioisotope Thermal electric Generators (RTGs)



Fission Reactors



Directed Energy






Things to be Mindful of When Designing an Electric Propulsion System

- Thrust, power, Isp
- Input power range
- Input voltage
- Propellant through capability (life)
- Exhaust plume characteristic
- Specific mass


The "Power" of Electric Propulsion

- JPL
 - ☐ The launch vehicle:
 - 40-m high
 - 230,000 kg
 - ☐ The Ion Propulsion System (IPS):
 - < 2-m high
 - 555 kg
 - ☐ The IPS operated ~75,000 times longer than the launch vehicle

EP Trajectories spread out the energy in time to reduce the required power




The Dawn IPS provided as much DV to the spacecraft as the launch vehicle



The 60-gallon propellant tank for the Dawn Ion Propulsion System (IPS) would fit in the trunk of your car


If high *Isp* is good, why not run at as high an *Isp* as possible?

- The propellant mass decreases exponentially with *lsp* (rocket equation)
- The power subsystem mass increases linearly with specific impulse
- This results in an optimum specific impulse for electric propulsion systems/missions





EP Enables Trades between Mass, Power, and Duty Cycle Margins




Deep Space Missions using Electric Propulsion





△V Beyond Earth Escape



Dawn BY THE NUMBERS

48,000 HOURS OF ION ENGINE THRUSTING

132+ GB SCIENCE DATA COllected

2,450 orbits around Vesta and Ceres

69,000 images taken


11.5 km/s ΔV

3.5 BILLION MILES TRAVELED since launch

2 new worlds EXPLORED










Commercial Spacecraft



Satellites with EP

- Nearly 600 spacecraft have been launched with electric propulsion
- Most are commercial satellites



Lev, D., et al, "The technological and commercial expansion of electric propulsion," Acta Astronautica 159 (2019) 213-227.



Boeing
All-Electric
Satellites





Future




Electric Propulsion has the Potential to Impact an Impressive Range of the Nation's Space Interests

- LEO Constellations
- Robotic Science Missions
- Human Exploration Missions
- Planetary Defense
- Asteroid Mining
- Rapid Transportation Throughout the Solar System

Robotic Science Missions DART Psyche CAESAR **Pre-Decisional Mission Concepts**



Deep Space SmallSats (< 100 kg)





Asteroid Retrieval Mission

Proposal for an Asteroid Return Mission study submitted in 2010

- 1. Project Title: Asteroid Return Mission
- 2. NASA Centers: JPL (lead), JSC (partner), GRC (partner)
- 3. External Partners: University of California at Santa Cruz (UCSC)
- 4. Proposal Leader:



Asteroid Redirect Mission

Feasibility Study

Final Report

24, 2013

Keck Institute for Space Studies Study Program Proposal

KISS Proposal submitted in 2011

Name of Study Program: Asteroid Return Mission Study

Date: January 17, 2011

Name of Caltech Campus Co-Lead: Fred Culick

Name of JPL Co-Lead: John Brophy

Name of External Co-Lead: Louis Friedman (The Planetary Society)

Estimated Budget for Study Program: \$66K

Description of the goals of this Study Program:

ibility of finding, characterizing, robotically capturing, rth Asteroid (NEA) to the vicinity of the Earth for of its resource potential, determination of its internal ant for planetary defense activities, and to serve as a

e vicinity of an asteroid. at several dozen candidate NEAs in the size range of

e final destination) will be known before the end of the t could be selected. One candidate mission option is to : International Space Station (ISS) in a total flight time a single launch by an Evolved Expendable Launch sulations indicate that to accomplish this would require (SEP) with a power level of approximately 40-kW at 1 n has a solar array that provides ~10-kW of power at 1 unication satellites have beginning-of-life solar array a 40-kW system is large, but not unreasonably so for a

	Organization						
r							
126	JSC						
260	UCSC						
113	JPL						
205	JPL						
432	GRC						
275	JPL						
579	JSC						
127	JPL						

NASA Feasibility study completed in 2013

Phase B


started 2016


Asteroid Redirect Robotic Mission **NASA Key Decision Point - B** Introduction





sion 2.0 Huntsville, Alabama

Pre-Decisional Mission Concept














High-power Hall Thrusters

HERMES Hall Thruster

- 12.5-kW, 2600-s Hall Thruster
- Currently under development by NASA / Aerojet Rocketdyne










Very High-power Hall Thrusters

NEXTStep 100-kWclass nested-Hall thruster





Planetary Defense

After discovery, this becomes primarily a propulsion problem




NEVER FORGET

12/21/65000000 b.c.


What size asteroids do we need to be concerned with?

Fireballs Reported by US Government Sensors

(1988-Apr-15 to 2017-Mar-11)




Most likely threat objects may turn out to be in the 50 m to 140 m dia





Planetary Defense Techniques






Ion Beam Deflection

Key Features

- lons act as kinetic impactors
- Applied force is independent of the asteroid characteristics
- Can engineer the applied force (power) and propellant usage (specific impulse)



Ion Beam Deflection Well Suited to Deflecting 50 to 140-m dia. Objects




Asteroid Mining

- Has long been recognized as a propulsion problem
- Probably only feasible in the long run if you can use asteroid-derived propellants




In Space Resource Utilization



Hutchison, R., "Meteorites, A Petrologic, Chemical and Isotopic Synthesis," Cambridge University Press, 2004, ISBN 0 521 47010 2.

Asteroid-Derived Hall Thruster Propellants



A magnesium-fueled Hall thruster from Michigan Technological University

	Molecular	Melting	Boiling	Ionization Energy						
	Weight	Point	Point	(eV)			Vapor Pressure			
	(AMU)	(C)	(C)	1st	2nd	Temperature	1 Pa	10 Pa	100 Pa	1000 Pa
Magnesium	24.31	650	1091	7.65	15.04	T (K)	701	773	861	971
Sulfur	32.06	115	445	10.36	23.34	T (K)	375	408	449	508
Xenon	131.3	-112	-108	12.13	21.21	T (K)	83	92	103	117



Rapid Transportation Throughout the Solar System




Three Key Features of an Architecture to Go Fast



Kilometer-scale Laser

Don't carry the power source laser beam power to the spacecraft








Light-weight PV Collector


Collect the laser power and convert it to electricity to power the ion drive sustem






Ultra-high Isp Thruster

Increase the exhaust velocity by a factor of 10 over the best ion engines today





A space-based laser beams power to a lithium-fueled, ultra-high specific impulse vehicle to enable rapid transportation throughout the solar system

Artist's concept

Pre-Decisional Mission Concept

Lithium-fueled ion engines

∟aser Beam

110-m diameter photovoltaic array with an areal density < 200 g/m²

Array cells tuned to the laser frequency for efficiency > 50%

Array output voltage of 6 kV

Lithium-fueled ion engines




LASER

High-power, space-based laser

- Phased array
- Kilometer-scale aperture
- 100's of megawatts

Beam Power Across the Solar System





Popular Mechanics

Humanity's Biggest Machines Will Be Built in Space

By Avery Thompson, Feb 16, 2018


"A mile-wide satellite might sound impossible, but that's exactly where the space industry is headed."



Human-scale Missions to Jupiter and Saturn

- Low α and high-power enables human-scale missions to Jupiter
- ~70,000 kg dry mass






Roundtrip TOF: 2.8 Years 180 days at Jupiter

- 1.15-yr outbound
- 0.5-yr stay
- 1.15-yr return

Saturn



Roundtrip TOF: 4.0 Years 180 days at Saturn

- 1.75-yr outbound
- 0.5-yr stay
- 1.75-yr return



